



Approved Form of Code in EM78260N

U8260N- _____ (Filled in by ELAN Sales)

The Following Items Filled in by Customer

- Customer's name: _____.
- Name of Program File: _____ .CDS.
Checksum : _____.
- Code Option Checksum,
Code Option 0: _____, Code Option 1: _____, Code Option 2: _____.
- Code Option Register (Please mark with "√" in the adequate blank)

Code Option 0

Bit	12	11	10	9	8	7	6	5	4	3	2	1	0
Mnemonic	-	-	-	TYPE	CLKS	ENWDTB	OSC2	OSC1	OSC0	HLP	-	-	-
Function	High	High	High		4clocks	Disable	High	High	High	High Power			
1	√	√	√										
Function	Low	Low	Low	260N	2clocls	Enable	Low	Low	Low	Low Power			
0				√							√	√	√

Code Option 1

Bit	12	11	10	9	8	7	6	5	4	3	2	1	0
Mnemonic	-	-	RCOUT	NRHL	NRE	WDTPS	CYES	C3	C2	C1	C0	RCM1	RCM0
Function	High	High	High	32/fc	Enable	18ms	2 Cycles	High	High	High	High	High	High
1	√	√						√	√	√	√		
Function	Low	Low	Low	8/fc	Disable	4.5ms	1 Cycle	Low	Low	Low	Low	Low	Low
0													

Code Option 2

Bit	12	11	10	9	8	7	6	5	4	3	2	1	0
Mnemonic	ID12	ID11	ID10	ID9	ID8	ID7	ID6	ID5	ID4	ID3	ID2	ID1	ID0
Function	High	High	High	High	High	High	High	High	High	High	High	High	High
1													
Function	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low
0													

*The range of the operating voltage: _____ V.

- Package Type: () P-DIP20; () N-SOP20; () H-DIE20.
- Intellectual Property Rights:

The customer (hereinafter "Party A") warrants that the product/code cosigned for manufacturing by ELAN Microelectronics Corporation (hereinafter "ELAN") are self-developed or legally assigned from third parties.



義隆電子股份有限公司
ELAN MICROELECTRONICS CORP.

HSIN-CHU: NO. 12 INNOVATION 1ST. RD
SCIENCE-BASED INDUSTRIAL PARK,
HSINCHU CITY, TAIWAN, R. O. C.
TEL: 886-3-563-9977 FAX: 886-3-563-9966
TAIPEI: 3F, NO. 178, MIN SHENG E. RD.
SEC, 2. TAIPEI, TAIWAN, R. O. C.
TEL: 886-2-25019108 FAX: 886-2-25019131

If ELAN infringes, or any third party claims that it's copyright, patent or other intellectual property rights (including trade secrets) have been infringed in the performance of this contract by the use, modification, copying, sales, or use of the in any other way by ELAN, or any machine language or program loaded into the Products by ELAN, Party A shall be responsible for all civil and criminal claims. Party A shall further indemnify ELAN for all damages or expenses it suffered in connection of the above.

7. Delivery Schedule: Date _____, Q'TY _____ PCS
Signature Customer: _____ Date: _____ Tel : _____
 ELAN Sales: _____ Date: _____
 ELAN FAE _____ Date: _____



Appendix 1: The Description of the Code Option Word

EM78260N has two CODE option words and one Customer ID word that are not a part of the normal program memory.

Code Option 0	Code Option 1	Code Option 2
Bit12~Bit0	Bit12~Bit11	Bit12~Bit0

1. Code Option Register (Code Option 0)

Bit12	Bit11	Bit10	Bit9	Bit8	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
-	-	-	TYPE	CLKS	ENWDTB	OSC2	OSC1	OSC0	HLP	-	-	-

- **Bit 12 ~ 10:** Not used (reserved).
These bits are set to "1" all the time
- **Bit 9 (TYPE):** Type selection.
0 = EM78260N
- **Bit 8 (CLKS):** Instruction time period option bit
0 = two oscillator time periods
1 = four oscillator time periods (default)
- **Bit 7 (ENWDTB):** Watchdog timer enable bit
0 = Enable
1 = Disable (default)
- **Bit 6, 5 & 4 (OSC2, OSC1 & OSC0):** Oscillator Modes Selection bits

Mode	OSC2	OSC1	OSC0
ERC ¹ (External RC oscillator mode); P54/OSCO acts as P54	0	0	0
ERC ¹ (External RC oscillator mode); P54/OSCO acts as OSC0	0	0	1
IRC ² (Internal RC oscillator mode); P54/OSCO acts as P54	0	1	0
IRC ² (Internal RC oscillator mode); P54/OSCO acts as OSC0	0	1	1
LXT ³ (Low XTAL oscillator mode)	1	1	0
HXT ³ (High XTAL oscillator mode) (default)	1	1	1

¹ Under ERC mode, OSC1 is used. P54 is defined by code option WORD0 Bit6 ~ Bit4.

² Under IRC mode, P55 is normal I/O pin. P54 is defined by code option WORD0 Bit6 ~ Bit4.

³ Under LXT, HXT, and ERC mode; OSC1 and OSC0 are used. These oscillator modes cannot use normal I/O pin.

NOTE

The transient point of system frequency between HXT and LXY is around 400 KHz.

- **Bit 3 (HLP):** Power consumption selection
0 = Low power consumption, applies to working frequency at 4MHz or below 4MHz.
1 = High power consumption, applies to working frequency above 4MHz.
- **Bit 2 ~ 0:** Reserved.
The bit 2 ~ 0 set to "0" all the time.

2. Code Option Register (Code Option 1)

Bit12	Bit11	Bit10	Bit9	Bit8	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
-	-	RCOUT	NRHL	NRE	WDTPS	CYES	C3	C2	C1	C0	RCM1	RCM0

- **Bits 12 ~ 11:** Not used (reserved). These bits are set to "1" all the time



- **Bit 10 (RCOUT):** System clock output enable bit in IRC or ERC mode
0 = OSCO pin is open drain
1 = OSCO output system clock

- **Bit 9 (NRHL):** Noise rejection high/low pulses define bit. INT pin is falling edge trigger
0 = Pulses equal to $8/f_c$ [s] is regarded as signal.
1 = Pulses equal to $32/f_c$ [s] is regarded as signal. (default)

NOTE

The noise rejection function is turned off under the LXT and sleep mode.

- **Bit 8 (NRE):** Noise rejection enable
0 = disable noise rejection
1 = enable noise rejection (default). However under Low XTAL oscillator (LXT) mode, the noise rejection circuit always disabled.

- **Bit 7 (WDTPS):** WDT Time-out Period Selection bit

WDT Time	Watch-Dog Time*
1	18 ms
0	4.5 ms

*Theoretical values, for reference only

- **Bit 6 (CYES):** Instruction cycle selection bit
0 = one instruction cycle
1 = two instruction cycles (default)
- **Bits 5, 4, 3 & Bit 2 (C3, C2, C1, & C0): Calibrator of internal RC mode.**
These bits must always be set to “1” only (auto calibration)

- **Bit 1 & Bit 0 (RCM1 & RCM0):** RC mode selection bits

RCM 1	RCM 0	Frequency(MHz)
1	1	4
1	0	8
0	1	1
0	0	455kHz

3. Customer ID Register (Code Option 2)

Bit 12~Bit 0
XXXXXXXXXXXXXX

- **Bits 12 ~ 0:** Customer's ID code